SAFETY DATA SHEET

PRO Max-Gloss 2K - Part B

Manufacturer
Seal 'n Lock System Corp.

Address
2401 Destiny Way, Odessa, FL 33556 USA

Issue date
August 11, 2026

Telephone
813-852-1500

Version
Version 1.0

Emergency
Poison Control Center: 1-800-222-1222

SECTION 1 - IDENTIFICATION

Item	Information
Product identifier	PRO Max-Gloss 2K - Part B
Other identification	Water-dispersible aliphatic polyisocyanate based on HDI
Recommended use	Professional/industrial paver, masonry or coating use as described on the product label.
Restrictions	Use only as directed. Not for ingestion or food-contact use.
Responsible party	Seal 'n Lock System Corp.; 2401 Destiny Way, Odessa, FL 33556 USA; 813-852-1500
Emergency number	Poison Control Center: 1-800-222-1222

SECTION 2 - HAZARD(S) IDENTIFICATION

OSHA HCS classification: Skin irritation Cat. 2; Skin sensitization Cat. 1; Eye irritation Cat. 2; Acute inhalation toxicity Cat. 4; Respiratory sensitization Cat. 1; STOT SE Cat. 3; Aquatic chronic Cat. 3

Label element	Information
Signal word	Danger
Pictogram(s)	Health hazard; Exclamation mark
Hazard statements	Causes skin irritation; May cause an allergic skin reaction; Causes serious eye irritation; Harmful if inhaled; May cause allergy or asthma symptoms or breathing difficulties if inhaled; May cause respiratory irritation; Harmful to aquatic life with long lasting effects
Precautionary statements	Avoid breathing mist or vapor; Use only with adequate ventilation; Wear protective gloves, clothing, and eye/face protection; In case of inadequate ventilation wear respiratory protection; If experiencing respiratory symptoms call a poison center or physician; Store locked up
Other hazards	Wet product may create a slip hazard. Spray mist may irritate the respiratory tract.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Concentration
HDI homopolymer / aliphatic polyisocyanate	28182-81-2	60-100%
Hydrophilic aliphatic polyisocyanate	666723-27-9	15-25%
Hexamethylene-1,6-diisocyanate	822-06-0	0.1-1%
N,N-dimethylcyclohexylamine	98-94-2	0.1-1%

Exact percentages and non-hazardous components may be withheld as trade secrets. Listed ranges reflect supplier information and formulation tolerances.

SECTION 4 - FIRST-AID MEASURES

Route	Measures
Inhalation	Remove immediately to fresh air. Call a poison center/physician. Respiratory sensitization symptoms may be delayed and can be life-threatening.
Skin	Remove contaminated clothing. Wash thoroughly with soap and water. Obtain medical attention for irritation or allergic reaction.
Eyes	Rinse cautiously with water for at least 15 minutes and obtain immediate medical attention.
Ingestion	Rinse mouth. Do not induce vomiting unless directed by medical personnel. Call a poison center or physician if unwell.

Most important symptoms/effects: May irritate skin, eyes, and respiratory tract. May cause permanent respiratory or skin sensitization. Asthma-like symptoms may be immediate or delayed.

SECTION 5 - FIRE-FIGHTING MEASURES

Suitable media: Use extinguishing media appropriate for the surrounding fire. Water spray, foam, dry chemical, or carbon dioxide may be used.

Specific hazards: Containers may rupture when heated. Combustion may produce carbon oxides, nitrogen oxides, smoke, and other irritating decomposition products.

Firefighter protection: Wear full protective equipment and self-contained breathing apparatus. Cool exposed containers with water spray.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Wear appropriate PPE. Stop the leak if safe. Prevent entry into drains, soil, and waterways. Contain with inert absorbent, collect in a compatible labeled container, and clean residue with water where appropriate. Wet surfaces may be slippery.

SECTION 7 - HANDLING AND STORAGE

Handling: Avoid eye and prolonged skin contact. Avoid breathing spray mist. Use adequate ventilation. Wash thoroughly after handling. Keep containers closed when not in use.

Storage: Store tightly closed at approximately 7-25 C (45-77 F), dry and protected from moisture. Do not reseal a container suspected of moisture contamination.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls: Provide general or local exhaust ventilation sufficient to control mist and vapor. Provide eyewash and washing facilities.

PPE: Wear chemical splash goggles, compatible protective gloves, and protective clothing. Where ventilation is inadequate or spray mist is generated, use respiratory protection selected under an OSHA-compliant respiratory-protection program.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Property	Value
Appearance	Clear to light-yellow liquid
Odor	Slight
Specific gravity	Approximately 1.15 at 20 C
Viscosity	Supplier data varies by grade/lot
Flash point	>100 C / >212 F
Water solubility	Reacts slowly with water; releases carbon dioxide

SECTION 10 - STABILITY AND REACTIVITY

Stable under recommended handling and storage conditions. Hazardous polymerization is not expected. Avoid extreme temperatures and water, alcohols, amines, strong bases, acids, and oxidizers. See Section 5 for combustion products.

SECTION 11 - TOXICOLOGICAL INFORMATION

May irritate skin, eyes, and respiratory tract. May cause permanent respiratory or skin sensitization. Asthma-like symptoms may be immediate or delayed.

SECTION 12 - ECOLOGICAL INFORMATION

Harmful to aquatic life with long-lasting effects. Avoid release.

SECTION 13 - DISPOSAL CONSIDERATIONS

Dispose of product, absorbents, and containers in accordance with applicable federal, state, and local requirements. Do not discharge to storm drains or natural waters.

SECTION 14 - TRANSPORT INFORMATION

Review package-specific DOT status. Regulated ground shipment may apply at or above reportable quantity; IMDG/IATA may be non-regulated for applicable package sizes.

SECTION 15 - REGULATORY INFORMATION

Prepared for U.S. workplace hazard communication. Users are responsible for determining all federal, state, and local requirements applicable to their use, packaging, and shipment.

SECTION 16 - OTHER INFORMATION

Date of Preparation: August 11, 2026 **Version:** 1.0

Abbreviations and Acronyms:

- **CAS:** Chemical Abstracts Service
- **GHS:** Globally Harmonized System of Classification and Labelling of Chemicals
- **OSHA:** Occupational Safety and Health Administration
- **PEL:** Permissible Exposure Limit
- **PPE:** Personal Protective Equipment
- **SDS:** Safety Data Sheet

Disclaimer: The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.